



深 圳 市 科 源 信 科 技 有 限 公 司

Shenzhen KeYuanXin Technology CO., LTD

产 品 规 格 书

SPECIFICATION FOR APPROVAL

深圳市福田区振华路 118 号华丽装饰一栋西座 306A
306A Block West Building 1, Huali Decoration
NO.118 Zhenhua Road Futian District Shenzhen
电话 TEL: 4008-735-535 传真 FAX: 0755-23616323



KEYUANXIN TECHNOLOGY GO.,LTD

Product Name: Crystal

Product Type: SMD 2520

Nominal Freq: 30.0000MHz

ProvideBrand: KKST

P/N: KAD30000B01R

Customer P/N:

Approved By Customer

Signature:

Date:



CONTENT

NO.1 Product specification and features

NO.2 Product outline dimension

NO.3 Product reliability

NO.4 Package specification








N0.1 Product specification and features


1.1 General characteristics	
Nominal frequency	30.000000 MHz
Overtone order	Fundamental
Type	SMD2520
Operating temperature	-20~70 °C
Storage temperature	-40~85 °C
1.2 Electric characteristics	
Adjustment tolerance: (at+25°C)	±10 ppm
Tolerance over the temperature:	±20 ppm
Load capacitance	10.0 pF
Drive level	10.0 μW
Equivalent resistance	40.0 Ω Max
Shut capacitance	7.0pF Max
Insulation resistance	500 M Ω Min 100VDC ± 15VDC
Aging	±3ppm/Year
1.3 Other characteristics	
SPDB	<-3 dB

NO.2 Outline dimensions、Appearances



2.1 Product outline dimension(mm)




2.2 Carrier Dimensional Drawing (mm)




2.3 Reel Dimensional Drawing (mm)



NO.3 Product reliability

Item	Condition	Result
A1	Cold resistance Stored at $-40\pm 2^{\circ}\text{C}$ for 1000 ± 2 hrs then $25\pm 2^{\circ}\text{C}$ 1~2 hrs before testing	(I)
A2	Heat resistance Stored at $85\pm 2^{\circ}\text{C}$ for 1000 ± 2 hrs then $25\pm 2^{\circ}\text{C}$ 1~2 hrs before testing	(I)
A3	Salt Mist Test Spray the $35^{\circ}\text{C}\pm 2^{\circ}\text{C}$ salt water (salt density 5%) to crystal for 48 ± 2 hrs,then clean by water	(I)
A4	Humidity Resistance Result Steady temperature: $60\pm 2^{\circ}\text{C}$;humidity: 90 ~ 95 % RH; time:500h	(I)
A5	Mechanical Shock 14700m/S^2 0.5sec 5times in each of 6 direction	(I)
A6	Aging Stored at $85\pm 3^{\circ}\text{C}$ for 720 ± 12 Hrs then $25\pm 2^{\circ}\text{C}$ 1~2 Hrs before testing Stored at $25\pm 2^{\circ}\text{C}$ for 1 ± 0.03 year	(I)
A7	Leakage Fine leak: Helium leak test *JIS C 6701 10.6	(V)
A8	Temperature Cycle $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$, Dewell 30Min, 100 cycles  The graph shows Temperature (°C) on the y-axis and Time on the x-axis. The cycle consists of three segments: a heating ramp to $150\pm 5^{\circ}\text{C}$, a dwell at $150\pm 5^{\circ}\text{C}$ for 120sec, and a heating ramp to $260\pm 5^{\circ}\text{C}$. The dwell at $260\pm 5^{\circ}\text{C}$ is indicated by a 10sec time marker. The cooling phase is labeled 'Cooling'.	(I)

3.1 Mechanism characteristics

B.1	Drop Test Device are dropped from a height of 100 cm onto 20mm thickness stainless plate executing 3 times of random drops	(I)
B.2	Resistance of Vibration Frequency: 10~55Hz, amplitude(total excursion): 1.5mm±15%,3 direction (X,Y,Z) each 2 hr	(I)
B.3	Resistance to soldering heat (Hand soldering method) Temperature: 370~400℃; Time: 3~4sec; Frequency: 2 times; Soldering iron: 60W/Min	(I)
B.4	Solderability 240±2℃, 3±0.5sec	(II)
B.5	Reflow) Resistance to soldering heat (Reflow) 260± 5℃; 10S; 2Times Reflow  The graph shows a temperature profile for reflow soldering. The y-axis is labeled 'TEMP. (°C)' with values from 50 to 300. The x-axis is labeled 'TIME (sec)'. - The temperature starts at 50°C and rises to 180°C. - A horizontal segment at 180°C is labeled '90-120S' with a pink double-headed arrow below it. - The temperature then rises to a peak of 260±5°C. - A horizontal segment at the peak is labeled '10s MAX'. - The temperature then falls to 230±5°C. - A horizontal segment at 230±5°C is labeled '40S'. - The temperature finally falls to 180±10°C.	(I)



Item	Result NO.	Specification Requirements
1	(I)	Frequency variation $\leq \pm 10\text{ppm}$ Resistance variation $< 5\Omega$ or 15% of RR spec., select the bigger value
2	(II)	The covering rate of Tin-plating is more than 95%
3	(III)	There is no bubbles after the Crystal is dipped in the water Insulation Resistance: 500 $M\Omega$ Min 100VDC/ $\pm 15\text{VDC}$
4	(IV)	The Crystal is no crackle under the observation of 10 times Magnifier.
5	(V)	$1 \times 10^{-9} \text{Pa.m}^3/\text{s}$ Max



NO.4 Package specification


4.1 Marking



4.2 Label

KKST KEYUANXIN TECHNOLOGY GO.,LTD		
Item	Crystal	QTY: 3000PCS
P/N	KAD30000B01R	
FREQUENCY	30.000MHz	DATE: 2017-09-12

4.3 Package specification





KEYUANXIN TECHNOLOGY GO.,LTD

浏览网址:WWW.SZKYX.CN